§54.01-2

(b) The material approved for incorporation by reference in this part and the sections affected are:

American Society of Mechanical Engineers (ASME) International

Three Park Avenue, New York, NY 10016—5990

Boiler and Pressure Vessel Code, section VIII, Division 1, Pressure Vessels, July 1989 with 1989 addenda 54.01–2; 54.01–5; 54.01–15; 54.01–18; 54.01–25; 54.01–30; 54.01–35; 54.03–1; 54.03–5; 54.05–1; 54.10–1; 54.10–3; 54.10–5; 54.10–10; 54.10–15; 54.15–10; 54.15–10; 54.15–13; 54.20–1; 54.25–25; 54.25–5; 54.25–8; 54.25–10; 54.25–15; 54.25–25; 54.25–3; 54.25–25; 54.30–3; 54.30–5; 54.30–5; 54.30–5; 54.30–10

American Society for Testing and Materials (ASTM)

100 Barr Harbor Drive, West Conshohocken, PA 19428–2959.

ASTM A 20/A 20M-97a, Standard Specification for General Requirements for Steel Plates for Pressure Vessels......54.05-10; 54.25-10

ASTM A 203/A 203M-97, Standard Specification for Pressure Vessel Plates, Alloy Steel, Nickel......54.05-20

ASTM A 370-97a, Standard Test Methods and Definitions for Mechanical Testing of Steel Products.............54.25-20

ASTM E 23-96, Standard Test Methods for Notched Bar Impact Testing of Metallic Materials......54.05-5

ASTM E 208-95a, Standard Test Method for Conducting Drop-Weight Test to Determine Nil-Ductility Transition Temperature of Ferritic Steels......54.05-5

Compressed Gas Association (CGA)

Manufacturers Standardization Society (MSS)

127 Park Street, NE. Vienna, VA 22180
SP-25, Standard Marking System for
Valves, Fittings, Flanges and
Unions, 1978......54.01-25

[CGD 88-032, 56 FR 35822, July 29, 1991 as amended by CGD 95-072, 60 FR 50462, Sept. 29, 1995; CGD 95-027, 61 FR 26000, May 23, 1996; CGD 96-041, 61 FR 50727, Sept. 27, 1996; CGD 97-057, 62 FR 51044, Sept. 30, 1997; USCG-1999-6216, 64 FR 53224, Oct. 1, 1999; USCG-1999-5151, 64 FR 67177, Dec. 1, 1999; USCG-2002-13058, 67 FR 61278, Sept. 30, 2002]

§ 54.01-2 Adoption of division 1 of section VIII of the ASME Code.

(a) Pressure vessels shall be designed, constructed, and inspected in accordance with division 1 of section VIII of the ASME (American Society of Mechanical Engineers) Code, as limited, modified, or replaced by specific requirements in this part. The provisions in the appendices to division 1 of section VIII of the ASME Code are adopted and shall be followed when the requirements in section VIII make them mandatory. For general information Table 54.01-1(a) lists the various paragraphs in division 1 of section VIII of the ASME Code which are limited, modified, or replaced by regulations in this part.

TABLE 54.01–1(A)—LIMITATIONS AND MODIFICA-TIONS IN THE ADOPTION OF DIVISION 1 OF SECTION VIII, ASME CODE

Paragraphs in Section VIII, ASME Code ¹ and disposition	Unit of this part
U-1 and U-2 modified by	54.01–5 through 54.01–
U-1(d) replaced byU-1(d) replaced by	54.01–5. 54.01–5(a) and 54.01– 15.
U-1(e) modified by	54.01–10. 54.01–15. 54.01–25. 54.01–30. 54.01–35. 54.01–40. 54.05–1. 54.10–1.
by. UG-92 through UG-103 modified by. UG-92 through UG-103 modified by.	54.10–1. 54.10–3. 54.10–3.
UG-98 reproduced by UG-99 modified by UG-100 modified by UG-115 through UG-120 modified	54.10–5. 54.10–10. 54.10–15. 54.10–1.
by. UG-116, except (k) replaced by UG-116(k) replaced by UG-117 replaced by UG-118 replaced by UG-118 modified by UG-120 modified by UG-125 through UG-134 modified by. UG-125 modified by UG-125 modified by UG-127 modified by UW-2(a) replaced by	54.10–20(a). 54.10–20(b). 54.10–20(c). 54.10–20(a). 54.10–20(d). 54.15–1 through 54.15–15. 54.15–10, 54.15–15. 54.15–13. 54.20–1. 54.01–5(b) and 54.20–2. 54.01–5(b).
UW-9(D) replaced by	54.20–3. 54.25–8. 54.20–5.

TABLE 54.01–1(A)—LIMITATIONS AND MODIFICA-TIONS IN THE ADOPTION OF DIVISION 1 OF SECTION VIII, ASME CODE—Continued

Paragraphs in Section VIII, ASME Code ¹ and disposition	Unit of this part
UB-1 modified by	54.23–1
UB-2 modified by	52.01-95(d) and 56.30-
	30(b)(1).
UCS-6 modified by	54.25–3.
UCS-25 replaced by	54.25–5.
UCS-56 modified by	54.25–7.
UCS-57, UNF-57, UHA-33, and UHT-57 modified by.	54.25–8.
UCS-65 through UCS-67 replaced by.	54.25–10.
UHA-23(b) and UHA-51 modified by.	54.25–15.
UHT-5(c), UHT-6, UHT-23 modified by.	54.25–20.
UHT-82 modified by	54.25-20, 54.25-25.
UA-60 modified by	54.15–3.

¹The references to specific provisions in the ASME Code are coded. The first letter "U" refers to division ¹ of section VIII. The second letter, such as "G", refers to a subsection within section VIII. The number refers to the paragraph within the subsection

(b) References to the ASME Code, such as paragraph UG-125, indicate:

U=Division 1 of section VIII, Pressure Vessels, ASME Code.

G=Part containing general requirements. 125=Paragraph within part.

- (c) When a paragraph or a section of the regulations in this part relates to material in division 1 of section VIII of the ASME Code, the relationship with the code will be shown immediately following the heading of the section or at the beginning of the paragraph as follows:
- (1) (Modifies $U_{\underline{}}$.) This indicates that the material in $U_{\underline{}}$ is generally applicable but is being altered, amplified or augmented.
- (2) (Replaces $U_{\underline{\hspace{1cm}}}$.) This indicates that $U_{\underline{\hspace{1cm}}}$ does not apply.
- (3) (Reproduces U____.) This indicates that U___ is being identically reproduced for convenience, not for emphasis.

[CGFR 68-82, 33 FR 18828, Dec. 18, 1968, as amended by CGFR 69-127, 35 FR 9976, June 17, 1970; CGFR 72-59R, 37 FR 6188, Mar. 25, 1972; CGD 72-206R, 38 FR 17226, June 29, 1973; CGD 73-254, 40 FR 40163, Sept. 2, 1975; CGD 77-147, 47 FR 21809, May 20, 1982; CGD 85-061, 54 FR 50963, Dec. 11, 1989. Redesignated by CGD 88-032, 56 FR 35822, July 29, 1991]

$\S 54.01-5$ Scope (modifies U-1 and U-2).

(a) This part contains requirements for pressure vessels. Table 54.01-5(a)

gives a breakdown by parts in this subchapter of the regulations governing various types of pressure vessels, boilers, and thermal units.

- (b) Pressure vessels are divided into Classes I, I–L (low temperature), II, II–L (low temperature), and III. Table 54.01–5(b) describes these classes and sets out additional requirements for welded pressure vessels.
- (c) The requirements for pressure vessels by class are as follows:
- (1) Class I-L and II-L pressure vessels must meet the applicable requirements in this part.
- (2) Pressure vessels containing hazardous materials as defined in §150.115 of this chapter must meet the requirements of this part or, as applicable, the requirements in 49 CFR parts 171–177 or part 64 of this chapter.
- (3) Except as provided in paragraph (c)(4) of this section, Classes I, II, and III pressure vessels not containing hazardous materials must be designed and constructed in accordance with the requirements in Section VIII, division 1, of the ASME Code and must be stamped with the ASME "U" symbol. These pressure vessels must also comply with the requirements that are listed or prescribed in paragraphs (d) through (g) of this section. Compliance with other provisions in this part is not required.
- (4) Classes II and III pressure vessels that have a net internal volume of less than 0.14 cubic meters (5 cubic feet) and do not contain hazardous materials must be stamped with either the ASME "U" or "UM" symbol. Compliance with other provisions in this part is not required.
- (d) Pressure vessels described in paragraph (c)(3) of this section must—
- (1) Have detailed plans that include the information required by §54.01-18 (approved by the Office of Management and Budget under OMB control number 2130-0181);
- (2) Meet §54.01–35, §54.20–3(c), and §54.25–3 of this part;
- (3) Have pressure relief devices required by subpart 54.15;
- (4) Meet the applicable requirements in §§ 54.10–3, 54.10–20, and 54.10–25 for inspection, reports, and stamping;